

# CCS REMBRANDT WATER COLOURS

## DESCRIPTION

CCS Rembrandt Water Colours are water based tints specifically designed to be applied to the CCS Stylepave Resurfacing System as a finishing stain.

The low odour, liquid colours can be used singularly or mixed with one another to form the desired colour tones. There are eight CCS Rembrandt Water Colours available including:

- Antique Green
- Aztec Red
- Bluestone
- Midnight
- Raw Umber
- Saxon Brown
- Sunflower
- Vanilla

## PACKAGING

CCS Rembrandt Water Colours are available in 1 litre bottles.

## COVERAGE

One litre of prepared CCS Rembrandt Water Colour (mixed 1:10) will cover approx. 8m<sup>2</sup>, over the CCS Stylepave Resurfacing System base, or approximately 5m<sup>2</sup> over a unsealed concrete base.

Estimated total coverage of a 1 litre bottle when prepared is 80m<sup>2</sup> over the CCS Stylepave Resurfacing System base, or approximately 50m<sup>2</sup> over a unsealed concrete base, depending on surface texture.

## APPLICATION

- 1 Shake the mixture well to ensure contents are dispersed evenly.
- 2 Mix singularly or with other CCS Rembrandt Colours to achieve the preferred tone.  
Please refer to the Rembrandt Colour Brochure for blending guidelines.
- 3 Then dilute the colour with water (no more than one part colour to 10 parts water) until the desired intensity is achieved.
- 4 Apply with a brush, squeegee, sponge or spray gun.
- 5 When completely dry, seal the area with an appropriate CCS sealer.

### PLEASE NOTE

The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses. To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexpert or negligent application, or ordinary wear and tear. Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.

## TECHNICAL INFORMATION

Solids	38% +/- 1% by volume
Thinning	Water
Appearance	Coloured liquid
Viscosity	3-3.5p
pH	8.5-9.0
Water Resistance	Extremely resistant
Solvent Resistance	May cause softening
MFFT	7°C

## LIMITATIONS

- Blending with CCS Stylepave colours is not recommended.
- Always ensure each coat is dry before applying subsequent coats.

For further information consult the Safety Data Sheet and read the product label carefully before use. Safety Data Sheets are available from [www.concretecoloursystems.com.au](http://www.concretecoloursystems.com.au) or by calling 1800 077 744.

## User Responsibility-Product Selection and Compatibility

CCS warrant that their manufactured product is free from defects as well as being suitable for the purpose for which it is intended as long as it has been used and applied in accordance with the most current Technical Data Sheet from CCS.

In practice, differences in materials, substrates and actual site conditions require an assessment of product suitability for the intended purpose.

The user is responsible for checking the suitability of products for their intended purpose.

Further, combinations of products that form a total system are often required to service particular applications. Due to the multitude of products available to service an application, only products from the CCS system of products must be used in combination with this product to ensure it will be suitable for the purpose for which it is intended.

The product must also not be mixed or used in combination with any other product which is not a product supplied by CCS.



CONCRETE®  
COLOUR  
SYSTEMS

A Division of River Sands Pty Ltd

BRISBANE (HEAD OFFICE)

Cnr Riverland & Monte Khoury Dr, Loganholme Qld 4129

Ph 1800 077 744 | (07) 3412 8111

[helpline@concretecoloursystems.com.au](mailto:helpline@concretecoloursystems.com.au)

[www.concretecoloursystems.com.au](http://www.concretecoloursystems.com.au)