

CCS GALAXY FLAKE SOLID COLOURS

DESCRIPTION

CCS Galaxy Solid Colour Flakes are coloured polymer flakes individually pigmented and asymmetrical in shape and size. CCS Galaxy Solid Colour Flakes are available in several popular primary colours and are added to the standard Galaxy Flake selection as a means of providing a range of customised colours.

ADDITION RATES

CCS Galaxy Solid Colour Flakes are usually added to the standard Galaxy Flakes at a rate of 10%, i.e. 500 grams to a 5kg box.

USES

A CCS Galaxy Flake Floor is suitable for residential, commercial and industrial applications in areas such as:

- Garages
- Patios
- Multi-purpose rooms
- Gyms
- Locker rooms
- Offices
- Warehouses
- Laboratories
- Retail shops
- Health facilities
- Educational facilities
- Showrooms
- Kitchens and laundries

FEATURES AND BENEFITS

- Durable
- Economical
- Slip Resistant
- Monolithic
- Low Sound
- Renewable

COVERAGE

Coverage depends on density and pattern required however typical coverage is 12-15m² per 5kg.

PERFORMANCE PROPERTIES

UV	UV Resistant
Solubility	Insoluble in water
SG	1.0 to 1.2
Shelf life	2 years minimum
Storage	Store in a cool, dry environment away from any moisture.

HANDLING

Use care when handling the flakes, especially when removed from box or pail. Rough handling or throwing may

break and create smaller particles. These small particles will change the appearance of the finish.

Care should be taken to avoid broadcasting a higher concentration of the smaller particles when completing the final sections of the floor.

For further information consult the Safety Data Sheet and read the product label carefully before use.

Safety Data Sheets are available from www.concretecoloursystems.com.au or by calling 1800 077 744.

User Responsibility-Product Selection and Compatibility

CCS warrant that their manufactured product is free from defects as well as being suitable for the purpose for which it is intended as long as it has been used and applied in accordance with the most current Technical Data Sheet from CCS.

In practice, differences in materials, substrates and actual site conditions require an assessment of product suitability for the intended purpose.

The user is responsible for checking the suitability of products for their intended purpose.

Further, combinations of products that form a total system are often required to service particular applications. Due to the multitude of products available to service an application, only products from the CCS system of products must be used in combination with this product to ensure it will be suitable for the purpose for which it is intended.

The product must also not be mixed or used in combination with any other product which is not a product supplied by CCS.

PLEASE NOTE

The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexperienced or negligent application, or ordinary wear and tear. Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.



CONCRETE
COLOUR
SYSTEMS

A Division of River Sands Pty Ltd

BRISBANE (HEAD OFFICE)

Cnr Riverland & Monte Khoury Dr, Loganholme Qld 4129

Ph 1800 077 744 | (07) 3412 8111

helpline@concretecoloursystems.com.au

www.concretecoloursystems.com.au