

CCS SEALER GRIP

DESCRIPTION

CCS Sealer Grip is a specially processed powder, which is designed to be used in conjunction with CCS Hardseal, Hi-Build Enduro, and their range of urethane and Epoxy sealers.

It combines with the sealer to form a textured finish which provides greater traction. In contrast to natural aggregates, sealer grip will not settle out when mixed with the sealer. This enables the applicator to seal and treat concrete and masonry surfaces.

RECOMMENDED USES

Use CCS Sealer Grip to increase skid resistance on relatively flat concrete surfaces.

Where the slope of the concrete exceeds a 30-degree angle, we recommend that either a broom finish be used on the concrete, or if this is not possible, an alternative coating with glass bead be applied.

Note: Slip Reduction Granules can be used with CCS Armourthane or CCS Armourgard SP, but not acrylic based sealers.

PACKAGING

CCS Sealer Grip is available in 280 gram bags.

APPLICATION GUIDELINES

- 1 The normal rate of application is 14–20 grams per litre (280 gms per 20 litre drum), however more or less can be added depending on the texture that is required.
- 2 Coat a small area, as a trial to ensure results are adequate.
- 3 Pour the required quantity of sealer grip powder slowly into the sealer whilst stirring with the other hand.
- 4 Continue stirring until thoroughly blended (usually within 3–5 minutes).

- 5 Ensure that the sealer grip is mixed into the selected sealer on the second coat of application only.

Note: Sealer Grip should not be added to the first coat of sealer as this will affect adhesion of the sealer to the substrate.

For further information consult the Safety Data Sheet and read the product label carefully before use.

Safety Data Sheets are available from www.concretecoloursystems.com.au or by calling 1800 077 744.

User Responsibility-Product Selection and Compatibility

CCS warrant that their manufactured product is free from defects as well as being suitable for the purpose for which it is intended as long as it has been used and applied in accordance with the most current Technical Data Sheet from CCS.

In practice, differences in materials, substrates and actual site conditions require an assessment of product suitability for the intended purpose.

The user is responsible for checking the suitability of products for their intended purpose.

Further, combinations of products that form a total system are often required to service particular applications. Due to the multitude of products available to service an application, only products from the CCS system of products must be used in combination with this product to ensure it will be suitable for the purpose for which it is intended.

The product must also not be mixed or used in combination with any other product which is not a product supplied by CCS

PLEASE NOTE

The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, inadequate preparation, inexpert or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.



CONCRETE
COLOUR
SYSTEMS

A Division of River Sands Pty Ltd

BRISBANE (HEAD OFFICE)
Cnr Riverland & Monte Khoury Dr, Loganholme Qld 4129

Ph 1800 077 744 | (07) 3412 8111
helpline@concretecoloursystems.com.au
www.concretecoloursystems.com.au